

Technical Data Sheet

EN

PUREX NG B**Issue date** 01.01.2019
Revision date 07.11.2019**Product description**

Component of polyurethane system, which contains a polymeric MDI. It is recommended for the production of rigid polyurethane foam.

State of aggregation	liquid
Colour	brown
Viscosity at 25°C [mPas]	150 - 250
Density at 20°C [g/cm ³]	1,23
Density at 25°C [g/cm ³]	1,23 ± 0,01

Transport and storage

Store in dry, well ventilated room, in tightly closed containers. Protect against moisture access and direct exposure to sunrays. Store away from heat sources, in the container originally packaged in a vertical position.

The products should be transported in tightly closed containers.

Containers opened before should be tightly closed and stored in position making out-flow impossible.

Permissible temperature during transport [°C]	5 - 25
Recommended storage temperature [°C]	15 - 25

Storage life from manufacture date, if stored in recommended conditions and in original containers: **6 months**

***Notes**

Data presented in this information have been obtained during the system foaming in model conditions. The results obtained when foaming in other conditions can be slightly different from published.

Every time the user is obliged to check the product and auxiliary agents usefulness for his intentional use.

The user is obligated to have a valid technical data sheet and safety data sheet of the product, which is provided by the manufacturer during the sale and every time on the customer's request.

Prior to processing the user must carefully read aforementioned documentation and follow the rules of procedure for product use.